

**BLANCO**




**VAINILLA**



**PERLA**



**ANTRACITA**



**MARFIL**



**VISÓN**



**GRIS**



**NEGRO**





**SEED**



**TERRA**

**MUESTRA DE CALIDAD / QUALITY SAMPLE**



**MARRÓN**



**NAVAL**



# cøpentek

— advance plus

toldo plus / awning plus

Lona especial para toldos reforzados con soporte acrílico apto para soportar condiciones climáticas adversas. Alta resistencia al agua.

Special fabrics for reinforced awnings with acrylic backing for advers weather conditions. With high water resistance.



Tejido de exterior, tapicería y toldo  
Outdoor furniture & sunhades fabrics

# cøpentek

— advance plus

Las lonas Cøpentek Advance Plus by Dralon® están diseñadas con un acabado especial de resina acrílica, que le confiere una columna de agua por encima de los 600 mm y una mayor resistencia tanto a la tracción como al desgarro, incrementado de este modo su durabilidad en el tiempo. Uso recomendado para toldos que exijan una mayor resistencia y que estén sometidos a condiciones climáticas más adversas.

Las lonas Cøpentek Advance Plus by Dralon® además de seguir un riguroso control de calidad a lo largo de todo el proceso de fabricación cumpliendo con todos los requisitos de homologación, están tratadas con productos antimicrobianos que ofrecen una óptima protección ante la aparición de microorganismos y poseen una excepcional resistencia al marcado de las arrugas.

#### PROTECCIÓN SOLAR\*

Las lonas Cøpentek Advance Plus by Dralon® protegen de la radiación ultravioleta con elevados porcentajes de filtrado. Dependiendo de la densidad, espesor y color, el porcentaje de protección varía.

*Factor de Protección Ultravioleta (UPF) de hasta +80 según la norma internacional UV Standard 801.*

#### MANTENIMIENTO\*

Para evitar la acumulación de suciedad en el tejido que pueda perjudicar al acabado y acelerar el deterioro, se recomienda realizar un lavado periódico con abundante agua, dejándolo secar al aire. No utilice detergentes ni productos con amoníaco o disolvente.

#### ACABADO\*

Resinado acrílico de alta tecnología por una cara. Acabado especial HQ anti manchas, anti moho y resistente al agua.

#### GARANTÍA\*

Cøpentek garantiza la lona Cøpentek Advance Plus by Dralon® por un periodo de 5 años, a contar desde la fecha de instalación.

\*Ver condiciones en anexo.

Cøpentek Advance Plus by Dralon® tarps are designed with a special acrylic resin finish that confers them with a water column of higher than 600 mm and higher tensile and tear strength, thus increasing its durability over time. Useful for awnings that require higher strength, subject to the most adverse weather conditions.

In addition to adhering to rigorous quality control throughout the entire manufacturing process, complying with all standardisation requirements, Cøpentek Advance Plus by Dralon® tarps are treated with anti-microbial products that offer optimal protection against the appearance of micro-organisms and have exceptional resistance to wrinkling.

#### SUN PROTECTION\*

Cøpentek Advance Plus by Dralon® tarps protect from ultraviolet radiation with high filtration percentages. Depending on the density, thickness, and colour, the percentage of protection may vary.

*Ultraviolet Protection Factor (UPF) of up to 80+ according to UV Standard 801.*

#### MAINTENANCE\*

To prevent the accumulation of dirt in the fabric that may harm the finish and accelerate deterioration, it is recommended that you wash the tarp periodically with abundant water and leave it to air dry. Do not use detergents or products with ammonia or solvents.





#### FINISH\*

High tech acrylic resin coating on one face. Special HQ, anti stain, anti mould, and water-resistant finish.

#### GUARANTEE\*

Cøpentek guarantees Cøpentek Advance Plus by Dralon® tarps for 5 years from the installation date.

\*See attached conditions.

Mantenimiento Fácil / Easy Care		   		
<b>Hilo / Yarn</b>	100% Fibra acrílica 100% Dralon® 100% Acrylic Fibre 100% Dralon®	<b>Repelencia al agua / Water Repellency</b> ≥5		
<b>Urdimbre / Warp Trama / Weave</b>	31 hilos x cm Nm 2/34.000 14 pasadas x cm Nm 2/34.000	<b>Resistencia a la tracción y alargamiento a la rotura</b>	Longitudinal / Lengthwise	Fuerza Máx (N) / Max average load (N) 1600
<b>Acabado / Finish</b>	Soporte acrílico / Acrylic support Especial HQ Anti bacterias / Anti manchas / Anti moho Special HQ Anti bacterias / Anti stain / Anti mildew	Determination of breakings strength and elongation	Transversal / Crosswise	Alargamiento a la fuerza máx (%) / Average elongation (%) 28'5 % 19,5 %
<b>Ancho / Width</b>	120 cm / 47" ± 1%	*UNE EN ISO 13934-1: 2013		
<b>Largo Pieza / Length of roll</b>	60 m / 65,64 yds	<b>Solidez del color a la luz / Colour Fastness to light</b> Grado / Grade 7/8 - 8 Escala Azules / Blue scale Grado / Grade 4/5 - 5 Escala Grises / Grey scale *UNE EN ISO 105 B02		
<b>Peso / Weight m²</b>	325 g /m² ± 5% *UNE 53352	<b>Solidez del color al agua clorada / Color fastness to chlorinated water</b> 5 sobre 5 *UNE EN ISO 105 E03		
<b>Columna hidrófuga / Waterproof column</b>	600 mm (refuerzo resina acrílica) / (acrylic resin reinforcement) *UNE EN ISO 20811	<b>Solidez del color al agua de mar / Color fastness to sea water</b> 5 sobre 5 *UNE EN ISO 105 E02		
<b>Repelencia al aceite / Oil Repellency</b>	≥5			



cøpente

COPEN FABRICS, SL  
NIF: B53475711  
Pol. Ind. Els Dos Pins, 03410 Biar, Alicante  
T. 965 81 12 05 / info@cøpentek.com  
www.cøpentek.com



Fabricado en España  
Made in Spain